

40 HP Enclosed Rotary Screw

160 CFM @ 125 PSI
155 CFM @ 150 PSI
72 DBA



Basic Compressor

Features

- Airend manufactured with German rotary screw components
- Spin on separator
- Spin on oil filter
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- UL Control components
- Automatic belt tensioning
- Omega profile rotors
- Heavy duty air filter
- Easy to access oil cooler for cleaning
- Operating pressures from 100-190 PSI available
- Extended oil drain with ball valve for easy service
- Easy to read and access gauges
- Factory filled with premium synthetic fluid
- Solid steel sound enclosure
- Vertical draft ventilation

Elite Compressor

Features

- All basic features
- Air/Oil cooler
- Automatic tank drain
- **SMART** contact controls
- Vibration isolation pads
- ASME powder coated air receiver
- Refrigerated air dryer
- Free freight in the 48 states & southern Canada

Model Number	Phase	Voltage	Tank	Elite/Basic	Length	Width	Height
RS403ENC	3	208-230-460	N/A	Basic	57	44	60
RS403ENC-E	3	208-230-460	120 Gallon Vertical	Elite	57	44	60

No Start Up Kit Required

See catalog for additional options



Compressed Air Systems

Simplicity. It's What We Do

www.compressed-air-systems.com

