

POWER KLEEN[®]

HIGH PERFORMANCE CLEANING EQUIPMENT

PORTABLE ELECTRIC HOT WATER

Model: KO-423E



PSI
PRESSURE SERVICES, INC.

Pressure Services, Inc.
2361 South Plaza Dr
Rapid City, SD 57702
605-341-5154

PORTABLE ELECTRIC HOT WATER

4 GPM @ 2,300 PSI
230 V, 1PH

Model: KO-423E



- 4 GPM @ 2,300 PSI Hot Water Portable Pressure Washer
- Welded Heavy Duty 1 1/4" OD Steel Tube Frame
- Durable Powder Coated Automotive Quality Paint Finish
- Horizontal Heat Chamber with Top Exhaust
- Stainless Steel Heat Shield and Burner Cover
- Painted Steel Heat Chamber Wrapper
- Exclusive Heat Chamber Insulation System
- Helical Heating Coil made of ASTM A53 Schedule 80 Steel Pipe
- Quick Coil Access
- High Efficiency Beckett Burner
- 12" Flat Free Tire and Engineered Truss Design Mag Wheels
- Water Separating Fuel Filter
- Corrosion Proof Molded Poly Fuel Tank (11 Gallon Capacity)
- 6 HP Electric Motor
- 230 Volt Single Phase
- Adjustable Temperature Control
- Exclusive High Impact Low Pressure Plumbing Manifold
- Belt Driven with Pump-Saver Clutch System
- General Pump - Model TS1511
- Stainless Steel Quick Couple Connections
- Quick Connect Stainless Steel Nozzles
- Low Pressure Chemical Injector
- Built in Hose Reel Socket
- 3/8" x 50' High Pressure Wire Braid 3,000 PSI Hose
- Dual Lance Wand
- Gun and Hose Holders
- Float Tank
- High Pressure Soap with Metering Valve
- 1 Year Limited Parts Warranty



Fuel Tank:
Corrosion proof polyethylene fuel tank



GFCI Protection:
Ground fault circuit interruption



Insulation System:
Innovative design for greater efficiency



Hose Reel Socket:
Incorporated directly to frame for max support



Pump-Saver Clutch System:
Eliminates bypass overheating



Flat-free Tires & Mag Wheels:
Holds up in the most rugged conditions

DISTRIBUTED BY:

PRODUCT SPECS

Operating Specs

Flow Output (GPM)	4
Max Pressure Rating (PSI)	2,300
Max Operating Temp	210 °F
Heat Rise	155 °F
Motor Horsepower	6
Nozzle Size	5.0

Electrical Requirements

Volt	230
Amp	30
Phase	1

Dimensions

Length	46"
Width	32"
Height	42"
Approx. Weight (lbs)	570

Oil Fired Burner System

Operating Fuel	Diesel
Input BTU's	384,000
Consumption (GPH)	1.65
Burner Fuel Capacity (Gal)	11
Exhaust	Top

