



9500 TWIN SERIES

MAKING WATER SOFT FOR OVER 40 YEARS

THE AUTOMATIC WATER CONDITIONER THAT GIVES YOU MORE!

9500 TWIN SERIES



- Ideal for apartments, large homes, motels, laundries, schools, restaurants and institutional applications where soft water is required 24/7
- Fully adjustable 5 cycle control delivers controlled upflow backwash, downflow brining, slow rinse, rapid rinse and downflow service
- Rugged, long life construction features lead free brass valve body
- Regenerates with soft water keeping the system clean for optimum operating efficiency and minimum maintenance
- Regenerates immediately when needed alternating tanks for soft water 24/7
- Available with 3200 mechanical or SXT electronic meter (shown)

Meter Specifications

Mechanical

METER SIZE	ACCURACY (±5%) RANGE (gpm)	CAPACITY RANGE STANDARD (gals)	CAPACITY RANGE EXTENDED (gals)
1"	0.70 - 40.0	310 - 5,270	1,150 - 26,350
1-1/2"	1.50 - 75.0	625 - 10,625	3,125 - 53,125
SXT Electronic		1 - 999,999 (Grains)	

Model Specifications	FC-150-T9500	FC-180-T9500	FC-240-T9500	FC-300-T9500	FC-360-T9500	FC-420-T9500	FC-480-T9500	FC-600-T9500
Exchange Capacity Per Tank Grain @ lb. Salt	Min. 50,000 @ 15	Min. 60,000 @ 18	Min. 80,000 @ 24	Min. 100,000 @ 30	Min. 120,000 @ 36	Min. 140,000 @ 42	Min. 160,000 @ 48	Min. 200,000 @ 60
	Med. 60,000 @ 20	Med. 72,000 @ 24	Med. 96,000 @ 32	Med. 120,000 @ 40	Med. 144,000 @ 48	Med. 168,000 @ 56	Med. 192,000 @ 64	Med. 240,000 @ 80
	Max. 75,000 @ 38	Max. 90,000 @ 45	Max. 120,000 @ 60	Max. 150,000 @ 75	Max. 180,000 @ 90	Max. 210,000 @ 105	Max. 240,000 @ 120	Max. 300,000 @ 150
Resin (Cu Ft) Per Tank	2.5	3.0	4.0	5.0	6.0	7.0	8.0	10.0
Mineral Tank Size	13" x 54"	14" x 65"	16" x 65"	18" x 65"	21" x 62"	21" x 62"	24" x 72"	24" x 72"
Brine Tank Size Salt Storage	18" x 40" 450 lbs.	24" x 41" 550 lbs.	24" x 50" 700 lbs.	24" x 50" 700 lbs.	24" x 50" 700 lbs.	24" x 50" 700 lbs.	24" x 50" 700 lbs.	24" x 50" 700 lbs.
Pipe Size	1.5"	1.5"	1.5"	1.5"	1.5"	1.5"	1.5"	1.5"
Flow Rate (Cont. 15 psi) (Peak 25 psi)	25 35	26 37	29 40	32 42	35 47	34 46	37 49	35 47
Backwash Rate	4.0 gpm	5.0 gpm	7.0 gpm	9.0 gpm	12.0 gpm	12.0 gpm	15.0 gpm	15.0 gpm

SOLD BY:



2361 S Plaza Drive, Rapid City, SD 57702-9385
(605) 341-5154 - (800) 666-3664 - Fax: (605) 341-4843