
PUMP STANDS



Pumping Equipment for Car & Truck Wash

Heavy Duty Steel Frame with Gloss Black, Powder Coat Finish and Stainless Steel Access Panels (3), which make our equipment built to last. Natural / LP On Demand Gas Fired 180,000 Input BTU Burner Systems generate approximately 130 deg. F water cost effectively. Belt driven, triplex oil bath pumps, float tanks and safety valves insure reliable performance. Unit comes standard with 2 solenoids (adjustable), that are remotely controlled by 24V. Optional electronic remote controls the pump, burner, and two chemical solenoids. Our Car Wash Stands are backed by the BEST Warranty in the industry.





Gas Valve, Float Tank, Relief Valve, High Limit Switch, and Control Fuses are conveniently located behind the



2361 South Plaza Drive Rapid City, SD 57702 605-341-5154 * 800-666-3664 * 605-341-4843 fax Visit our web site at: www.pressureservices.com

High Limit Switch

Prevents overheating

Weep Control Valve

Prevents lines

Removable Tray


Provides easy access to pilot light

Motor and Motor Protection

Continuous duty motor with overload protection

Chemical Solenoids

Provide high pressure chemical injection for soap, wax, and other chemicals compatible with pump materials



Pressure Relief Valves

Prevent excessive pressure buildup from overheat and frozen or plugged

Pump Switch

Turns pump on for washing

Vacuum Safety Switch

Turns off burner during no flow

Tri-Plunger Pump

Oil bath crankcase with forged brass manifold

Pump Base

Shock mounted to minimize vi-

PUMP STAND SPECIFICATIONS

| MODEL | 32315 | 32416 | 32320 | 32423 | 32430 |
|------------------------|-------------------------|-------|-------|---------|---------|
| DISCHARGE PRESSURE PSI | 1500 | 1600 | 2000 | 2300 | 3000 |
| FLOW GPM | 3 | 4 | 3 | 4 | 4 |
| OPERATING TEMPERATURE | 140 F | 130 F | 140 F | 130 F | 130 F |
| INPUT B.T.U. PER HOUR | 180,000 6" Vent | | | | |
| BURNER | Natural Gas or LP | | | | |
| COIL | Sched 80 | | | | |
| PUMP | Triplex Ceramic Plunger | | | | |
| PUMP MOTOR HP | 4 | 4 | 4 | 6 | 8 |
| VOLTS / PHASE | 230V / 1 or 3 Phase | | | | |
| TOTAL AMPERAGE 1Ph/3Ph | 26/17 | 26/17 | 26/17 | 36 / 20 | 40 / 25 |
| DEPTH / WIDTH / HEIGHT | 28" / 32" / 60" | | | | |
| NET WEIGHT | 580 | 580 | 580 | 600 | 620 |



2361 South Plaza Drive Rapid City, SD 57702 605-341-5154 * 800-666-3664 * 605-341-4843 fax Visit our web site at: www.pressureservices.com