



INNOVATIVE SOLUTIONS TODAY FOR A MORE PROFITABLE TOMORROW

Reconditioned Pressure Washer/Car Wash Stands Include the Following:

High Pressure Pump

High Pressure Pump – New Packings
High Pressure Pump – New Oil Seals
High Pressure Pump – New Valves
High Pressure Pump – Oil Changed

Electric Motor for Pump

Electric Motor - Amp Draw Is Checked and Compared to What Amps the Unit Should Draw. If Motor Shows Excessive Amp Draw, Motor Is Taken to an Authorized Motor Repair Shop and Is Rebuilt or Is Replaced by Pressure Services.

Heating Coil

Coil is checked for back pressure indicating restriction from scale build-up. Coil is cleaned, flushed, and back pressure is re-checked until acceptable. If coil is bad it is replaced.

Hose/Gun/Wand/Tips

New 50 Ft High Pressure Hose, Gun, Wand, and Spray Tips (Does not Apply to Car Wash Stands).

Burner System

Oil Fired

Fuel Filter – Replaced
Fuel Pump – Operating Pressure Verified
Air/Fuel Band Adjustment – Adjustment is Made for Optimum Performance
Fuel Nozzle – Replaced
Fuel Tank – Drained and Cleaned to Eliminate Any Contamination
Exterior of Coil Checked for Soot and Cleaned if Necessary

LP or Natural Gas Fired

Actuator on Gas Valve Tested
Exterior of Coil Checked for Soot and Cleaned if Necessary

Solenoids

Soap Solenoids on Pressure Washers (If Applicable) - Replaced
Soap/Wax Solenoids on Car Wash Stands – Replaced