



120-Gallon Air Compressors

Two Stage – Electric – Duplex



The duplex horizontal 120-gallon units are specifically designed to finish jobs quickly and efficiently in workshops, service bays and more.

COMPRESSOR PUMP

- Cast iron compressor pump
- Splash lubricated
- Stainless-steel braided discharge hose
- Large cartridge intake filter
- Oil level sight indicator

MOTOR

- Industrial low RPM motor
- Magnetic start for thermal overload protection

FRAME

- Powder coated ASME receiver tank
- $\frac{3}{16}$ -inch base plate to reduce vibration
- Powder coated two-piece belt guard

COMPONENTS

- ASME safety valves
- Tank pressure gauge
- Hour meter
- Large fly wheel
- Intake filter/silencer
- Tank shut-off valve
- 3 position switch – compressor 1 (lead motor pump), automatic alternating and compressor 2 (lead motor pump)

LIMITED WARRANTY

- 1 year motor

CERTIFICATION

- ASME Boiler and Pressure Vessel Code – U



120-Gallon

Air Compressors – Two Stage – Electric – Duplex

MODEL NUMBER	CFM @ PSI	HORSEPOWER/MOTOR	PUMP RPM	DIMENSIONS (LxWxH)	BOLT DOWN (LxW)	SHIP WT.	NET WT.
36.0 @ 175	5.0 HP, 230V, 10, 46.0A	860	74x26.5x58in.	34.5x23.5in.	1013 lb.	909 lb.	
36.0 @ 175	5.0 HP, 200V, 30, 32.2A	860	74x26.5x58in.	34.5x23.5in.	953 lb.	849 lb.	
36.0 @ 175	5.0 HP, 230V, 30, 27.6A	860	74x26.5x58in.	34.5x23.5in.	925 lb.	821 lb.	
36.0 @ 175	5.0 HP, 460V, 30, 13.8A	860	74x26.5x58in.	34.5x23.5in.	925 lb.	821 lb.	
46.4 @ 175	7.5 HP, 230V, 10, 62.0A	1250	74x26.5x58in.	34.5x23.5in.	1049 lb.	945 lb.	
46.4 @ 175	7.5 HP, 200V, 30, 46.0A	1250	74x26.5x58in.	34.5x23.5in.	1091 lb.	987 lb.	
46.4 @ 175	7.5 HP, 230V, 30, 40.0A	1250	74x26.5x58in.	34.5x23.5in.	969 lb.	865 lb.	
46.4 @ 175	7.5 HP, 460V, 30, 20.0A	1250	74x26.5x58in.	34.5x23.5in.	969 lb.	865 lb.	
68.4 @ 175	10.0 HP, 230V, 10, 78.0A	990	74x26.5x58in.	34.5x23.5in.	1373 lb.	1223 lb.	
68.4 @ 175	10.0 HP, 200V, 30, 61.6A	990	74x26.5x58in.	34.5x23.5in.	1333 lb.	1183 lb.	
68.4 @ 175	10.0 HP, 230V, 30, 53.6A	990	74x26.5x58in.	34.5x23.5in.	1313 lb.	1163 lb.	
68.4 @ 175	10.0 HP, 460V, 30, 26.8A	990	74x26.5x58in.	34.5x23.5in.	1313 lb.	1163 lb.	
93.0 @ 175	15.0 HP, 200V, 30, 88.0A	810	74x26.5x58in.	34.5x23.5in.	1736 lb.	1586 lb.	
93.0 @ 175	15.0 HP, 230V, 30, 76.0A	810	74x26.5x58in.	34.5x23.5in.	1706 lb.	1556 lb.	
93.0 @ 175	15.0 HP, 460V, 30, 38.0A	810	74x26.5x58in.	34.5x23.5in.	1706 lb.	1556 lb.	

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
	Replacement pump	
	Replacement pump	
	Replacement pump	

OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
	Vibration isolator pads – Isolators protect the unit from vibration during use	
	Electric tank drain – Automatically drains liquid from compressor tank; recommended to use with an after cooler	
	Pneumatic tank drain – Automatically drains liquid from compressor tank; recommended to use with an after cooler	
	After cooler – Removes up to 65% of the moisture from discharged compressed air and drops the temperature within 10°F of ambient	
	After cooler – Removes up to 65% of the moisture from discharged compressed air and drops the temperature within 10°F of ambient	
	After cooler – Removes up to 65% of the moisture from discharged compressed air and drops the temperature within 10°F of ambient	
	Low oil monitor – Low oil sensor does not allow unit to start when oil levels fall below an adequate level	
	Low oil monitor – Low oil sensor does not allow unit to start when oil levels fall below an adequate level	
	Low oil monitor – Low oil sensor does not allow unit to start when oil levels fall below an adequate level	
	Low oil monitor – Low oil sensor does not allow unit to start when oil levels fall below an adequate level	
	Low oil monitor – Low oil sensor does not allow unit to start when oil levels fall below an adequate level	
	Low oil monitor – Low oil sensor does not allow unit to start when oil levels fall below an adequate level	



 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.