





30, 80-Gallon & Base-Mount Air Compressors

Two Stage — Gasoline



Commonly used for industrial and automotive applications, these air compressors can be mounted in the back of a trailer or service truck to take to the most demanding jobsites.

COMPRESSOR PUMP

- Cast iron compressor pump
- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

ENGINE

- Electric start – battery and cables not included

FRAME

- Powder coated ASME receiver tank (Tank-mount models)
- $\frac{3}{16}$ -inch base plate to reduce vibration
- Powder coated two-piece belt guard
- Removable base plate offers flexible installation

COMPONENTS

- Regulator and two gauges for tank and outlet pressure
- ASME safety valves
- 16½-inch fly wheel
- Tank drain valve
- Service truck mount kit (Standard on base-mount models)

LIMITED WARRANTY

- 3 year engine

CERTIFICATIONS

- ASME Boiler and Pressure Vessel Code – UM (30-gallon models)
- ASME Boiler and Pressure Vessel Code – U (80-gallon models)



30, 80-Gallon & Base-Mount Air Compressors – Two Stage – Gasoline

TANK-MOUNT MODELS

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
29.0 @ 175	389cc Honda GX390 OHV+	30-gallon	Pneumatic	38x23x46in.	480 lb.	416 lb.	
29.0 @ 175	429cc Kohler CH440 OHV	30-gallon	Cable throttle	38x23x46in.	480 lb.	416 lb.	
29.0 @ 175	420cc Mi-T-M OHV	30-gallon	Pneumatic	38x23x46in.	480 lb.	416 lb.	
29.0 @ 175	389cc Honda GX390 OHV+	80-gallon	Pneumatic	52x26.5x53in.	560 lb.	496 lb.	
29.0 @ 175	420cc Mi-T-M OHV	80-gallon	Pneumatic	52x26.5x53in.	560 lb.	496 lb.	

BASE-MOUNT MODELS

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
29.0 @ 175	389cc Honda GX390 OHV+	Base-mount	Pneumatic	36.5x19x28in.	279 lb.	215 lb.	
29.0 @ 175	420cc Mi-T-M OHV	Base-mount	Pneumatic	36.5x19x28in.	279 lb.	215 lb.	

*Equipped with 150-PSI maximum rated regulator.

+49 state engine. Not for sale in California.

ACCESSORY:

PART NUMBER	DESCRIPTION	FITS MODELS
	Equipment cover – Keeps your equipment clean, dry and looking like new	

OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
	Battery, battery tray, box and 2-foot of cables – Attaches to engine side of unit	
	Battery tray, box and 2-foot of cables – Attaches to engine side of unit	
	Vibration isolator pads – Recommended for models mounted in service truck applications. Isolators protect the unit from vibration during use.	
	Remote start/choke – 7-foot wire extension for key switch	
	Remote start/choke, sealed cable – 7-foot wire extension for key switch	
	Remote start/choke, sealed cable – 7-foot wire extension for key switch	

