



30-Gallon & Base-Mount

Air Compressors

Two Stage — Gasoline



Designed with a powder coated ASME receiver tank, you will experience proven performance from the 30-gallon and base-mount air compressors time after time.

COMPRESSOR PUMP

- Cast iron compressor pump
- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

FRAME

- Powder coated ASME receiver tank
- $\frac{3}{16}$ -inch base plate to reduce vibration
- Powder coated two-piece belt guard

COMPONENTS

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 16½-inch fly wheel
- Quality pilot valve unloader

LIMITED WARRANTY

- 3 year engine

CERTIFICATION

- ASME Boiler and Pressure Vessel Code – UM



30-Gallon & Base-Mount

Air Compressors – Two Stage – Gasoline

STATIONARY MODELS

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
	17.2 @ 175	270cc Honda GX270 OHV+	30-gallon	Pneumatic	40.5x17.5x44.5in.	446 lb.	376 lb.
^	17.2 @ 175	270cc Honda GX270 OHV+	30-gallon	Pneumatic	40.5x17.5x44.5in.	460 lb.	390 lb.
	17.2 @ 175	300cc Mi-T-M OHV	30-gallon	Cable throttle	40.5x17.5x44.5in.	434 lb.	364 lb.
^	17.2 @ 175	300cc Mi-T-M OHV	30-gallon	Cable throttle	40.5x17.5x44.5in.	449 lb.	379 lb.

**49 state engine. Not for sale in California.*

BASE-MOUNT MODEL

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
^	17.2 @ 175	300cc Mi-T-M OHV	Base-mount	Cable throttle	36.5x21x32in.	379 lb.	309 lb.

^Equipped with electric start – battery, box and cables not included.

**Equipped with 150-PSI maximum rated regulator.*

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
	Service truck mount kit – Includes four rubber isolators to reduce wear. Recommended for models mounted in service truck applications	
	Equipment cover – Keeps your equipment clean, dry and looking like new	

OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
	Manual drain/regulator/metal bowl – Drains moisture from air system	
	Battery, battery tray, box and 2-foot of cables – Attaches to engine side of unit	
	Battery tray, box and 2-foot of cables – Attaches to engine side of unit	
	Remote start/choke – 7-foot wire extension for key switch	
	Remote start/choke, sealed cable – 7-foot wire extension for key switch	
	Remote start/choke, sealed cable – 7-foot wire extension for key switch	

