



30-Gallon

Air Compressors

Two Stage — Diesel



This two stage diesel-powered air compressor provides consistent and reliable air power for industrial, automotive and service body applications.

COMPRESSOR PUMP

- Cast iron compressor pump
- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

ENGINE

- Electric start – battery, box and cables not included
- Glow plug equipped for easy starting in cold temperatures

FRAME

- Powder coated ASME receiver tank
- $\frac{3}{16}$ -inch base plate to reduce vibration
- Powder coated two-piece belt guard
- Removable base plate offers flexible installation

COMPONENTS

- Regulator and two gauges for tank and outlet pressure
- ASME safety valves
- Tank drain valve

LIMITED WARRANTY

- 3 year engine

CERTIFICATION

- ASME Boiler and Pressure Vessel Code – UM



30-Gallon

Air Compressors – Two Stage – Diesel

| MODEL NUMBER | CFM @ PSI* | HORSEPOWER/ENGINE | ENGINE IDLE CONTROL | DIMENSIONS (LxWxH) | SHIP WT. | NET WT. |
|--------------|------------|-------------------------|---------------------|--------------------|----------|---------|
| | 29.0 @ 175 | 9.1 HP Kohler KD440 OHV | Cable throttle | 38x23x46.5in. | 540 lb. | 483 lb. |

*Equipped with 150-PSI maximum rated regulator.

ACCESSORY:

| PART NUMBER | DESCRIPTION | FITS MODEL |
|-------------|--|------------|
| | Equipment cover – Keeps your equipment clean, dry and looking like new | |

OPTIONS:

| PART NUMBER | DESCRIPTION | FITS MODEL |
|-------------|---|------------|
| | Battery box, cables and tray – Attaches to engine side of unit | |
| | Vibration isolator pads – Recommended for models mounted in service truck applications. Isolators protect the unit from vibration during use. | |

