



30-Gallon

Air Compressor/ Generator Combinations

Two Stage — Gasoline



The 30-gallon two stage air compressor/generators tie two units into one for optimal power remodelers, contractors and DIYers appreciate.

COMPRESSOR PUMP

- Cast iron compressor pump
- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- Oil level sight indicator

GENERATOR

- Brushless alternator
- Total harmonic distortion (THD) less than 6%
- 100% copper windings
- (2) NEMA 5-20R 120V, 20A and (1) NEMA L6-20R 240V, 20A receptacles

FRAME

- Powder coated ASME receiver tank
- $\frac{3}{16}$ -inch base plate to reduce vibration
- Powder coated two-piece belt guard

COMPONENTS

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 16½-inch fly wheel
- Quality pilot valve unloader

LIMITED WARRANTY

- 3 year engine

CERTIFICATION

- ASME Boiler and Pressure Vessel Code – UM



30-Gallon

Air Compressor/Generator Combinations – Two Stage – Gasoline

MODEL NUMBER	CFM @ PSI	CFM @ PSI*	MAX. AC OUTPUT	ALTERNATOR WATTAGE		DISPLACEMENT/ENGINE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
				CONT. WITH COMP. ON-LOAD	CONT. WITH COMP. OFF-LOAD				
	16.4 @ 90	15.7 @ 175	4000 watts	2300 watts	3500 watts	389cc Honda GX390 OHV+	40x24.5x45in.	550 lb.	450 lb.
^	16.4 @ 90	15.7 @ 175	4000 watts	2300 watts	3500 watts	389cc Honda GX390 OHV+	40x24.5x45in.	557 lb.	457 lb.
	16.4 @ 90	15.7 @ 175	4000 watts	2300 watts	3500 watts	429cc Kohler CH440 OHV	40x24.5x45in.	550 lb.	450 lb.
^	16.4 @ 90	15.7 @ 175	4000 watts	2300 watts	3500 watts	429cc Kohler CH440 OHV	40x24.5x45in.	557 lb.	457 lb.
	16.4 @ 90	15.7 @ 175	4000 watts	2300 watts	3500 watts	420cc Mi-T-M OHV	40x24.5x45in.	550 lb.	450 lb.
^	16.4 @ 90	15.7 @ 175	4000 watts	2300 watts	3500 watts	420cc Mi-T-M OHV	40x24.5x45in.	557 lb.	457 lb.
	16.4 @ 90	15.7 @ 175	4000 watts	2300 watts	3500 watts	408cc Vanguard OHV	40x24.5x45in.	550 lb.	450 lb.
^	16.4 @ 90	15.7 @ 175	4000 watts	2300 watts	3500 watts	408cc Vanguard OHV	40x24.5x45in.	557 lb.	457 lb.

*Equipped with 150-PSI maximum rated regulator. +49 state engine. Not for sale in California. ^Equipped with electric start – battery, box and cables not included.

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
	Engine oil drain extension – 14-inch flexible drain hose makes oil changes clean and easy	
	Equipment cover – Keeps your equipment clean, dry and looking like new	

OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
	Battery, battery tray, box and 2-foot of cables – Attaches to engine side of unit	
	Lifting hook – For easier portability	
	Idle down – When activated it automatically throttles down engine to conserve fuel	
	Battery tray, box and 2-foot of cables – Attaches to engine side of unit	
	Idle down – When activated it automatically throttles down engine to conserve fuel	
	Idle down – When activated it automatically throttles down engine to conserve fuel	
	Vibration isolator pads – Isolators protect the unit from vibration during use. Recommended for models mounted in service truck applications.	
	Remote start/choke – 7-foot wire extension for key switch	
	Remote start/choke, sealed cable – 7-foot wire extension for key switch	
	Remote start/choke, sealed cable – 7-foot wire extension for key switch	
	Remote start/choke, sealed cable – 7-foot wire extension for key switch	



NEMA 5-20R
125V



NEMA L6-20R
240V

 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.