



www.komfg.com

KO MANUFACTURING INC.


ANTIFOAM

PRODUCT NUMBER 295



RESEARCH

Through R&D and field testing, KO Chemists combine creativity with technology to bring you products with the performance you require. Using our sophisticated KO lab we continually test new products, existing products, and our manufacturing processes for effectiveness and affordability. When a new product meets our requirements, it goes to a select group of end-users for real-world evaluation. Only after testing, evaluating, and re-testing is a KO product ready for distribution. We invite you to come and be a part of a winning solution.



Attention: Refer to our Material Safety Data Sheet regarding hazards, personal protection, and disposal of this product.

Techsheat Modified on 2/3/2003

PRODUCT DESCRIPTION:

AntiFoam is an exceptional silicone based defoaming agent. Foaming is immediately suppressed with even a small quantity of chemical for long periods of time. Antifoam is ideal for industrial spray cabinets, soak tanks, decorative fountains, cutting fluids, or any other application where defoaming is required.

INSTRUCTIONS:

To suppress foaming in most situations, add 1 ounce of AntiFoam per 1000 gallons of water. Since nearly all applications differ, more or less chemical may be required.

To suppress thick foam that has already been generated, dilute 1/2 ounce of AntiFoam with 1 gallon of water. Spray mist over foam. Foam should dissipate immediately. Adjust amount of chemical if necessary.

This product will adversely affect painting processes creating fish eyes, scales, etc. Do not use this product on parts that are being prepared for painting or in buildings where painting is performed.

CUSTOMER BENEFITS:

- Easy to use.
- Provides excellent foam suppression.
- Long lasting.
- Cost effective.
- Highly dilutable.