Jabs™

PRODUCT NUMBER 429

PRODUCT DESCRIPTION:

Jabs[™] is a Drum-in-Box kit designed for the general purpose cleaning of nearly any surface. The Drum-in-Box concept is designed to allow the customer to mix their own drums of liquid detergent. Jabs[™] is unique from other kits because it features two easy-mix liquid containers. Also, Jabs[™] Hyperstack[™] technology allows two kits to be mixed into one drum for an ultra-concentrated cleaner. Jabs[™] is truly a unique product that offers the customers a variety of applications.

KEY POINTS:

Biodegradable
Easy shipping and handling
Hyperstackable
Non-toxic.
Safe on nearly all surfaces
USDA approved
Wide variety of applications

Attention: Refer to our Material Safety Data Sheet regarding hazards, personal protection, and disposal of this product.

Techsheet Modified on 5/10/2006

PRODUCT INSTRUCTIONS:

Directions:

- 1) Dilute with hot or cold water using the guidelines below.
- 2) Apply diluted Jabs[™] to surface & let sit for 60 seconds.
- 3) Wipe or Rinse off. Do not let product dry on surface.
- 4) Repeat steps 1 through 3 if necessary.

Dilutions may vary with different cleaning tasks. Try the General Cleaning recommended dilution first; then strengthen or repeat if necessary.

Dilutions Chart

Surface: (General Cleaning:		*Heavy Cleaning:	
	Mixing Options:		Mixing Options:	
Surface:	#1"Hyper	r''	#1	
Painted Aluminum	32:164:1	2:1	4:1	
(Vehicles, Boats, Siding)				
Stone	32:164:1	2:1	4:1	
Concrete	16:132:1	Undilut	ed	1:1
Stucco	32:164:1	2:1	4:1	
Brick	16:132:1	2:1	4:1	
Asphalt	16:132:1	Undiluted 1:1		1:1
Roofing	16:132:1	2:1	4:1	
FRP Board	32:164:1	2:1	4:1	
Treated Outdoor Wo	od 16:132:1	2:1	4:1	
(Decks & Fencing)				
Ceramic Tile	32:164:1	2:1	4:1	
Porcelain	32:164:1	2:1	4:1	
Chrome	32:164:1	2:1	4:1	
Steel	32:164:1	2:1	4:1	
Stainless Steel	32:164:1	2:1	4:1	
Plastic	32:164:1	2:1	4:1	
Fiber Glass	32:164:1	2:1	4:1	
Canvas	16:132:1	2:1	4:1	
Carpet	64:1128:1	32:1	64:1	
Vinyl Tile	32:164:1	2:1	4:1	
Rubber	16:132:1	Undilut	ed	1:1
Other Painted Surfac	es 32:164:1	2:1	4:1	

^{*}For extremely heavy soils, rinse surface first, apply $Jabs^{TM}$, scrub if necessary, & rinse clean.

If in doubt, spot test on hidden surface first.

For uncoated, soft metals such as aluminum, brass, copper, galvanized metel, magnesium, & zinc use at 64:1 for General Cleaning and 4:1 for Heavy Cleaning.