

Series Series

SPECIFICATIONS

Oil Fired Portable Pressure Washer

	GENERAL					ELECTRICAL			BURNER SYSTEM		DIMENSIONS/WEIGHT			
Model	Туре	GPM	PSI	HP	Drive	Volt	AMP	Ph.	BTU	Stack Size	L	W	Н	LBS.
14-310C	SS	3	1000	2.3	Belt	115	20	1	479,000	8"	37.5"	29"	44.5"	540
14-320C	SS	3	2000	4	Belt	230	20	1	479,000	8"	37.5"	29"	44.5"	560
14-416	SS-SC	4	1600	4	Belt	230	20	1	384,000	8"	37.5"	29"	44.5"	455
14-423	SS-SL-SC	4	2300	6/7.5	Belt	230/440	30/20/15	1/3	384,000	8"	37.5"	29"	44.5"	535
14-430	SS-SL-SC	4	3000	8/7.5	Belt	230/440	40/30/20	1/3	384,000	8"	37.5"	29"	44.5"	545
14-525	SS-SL-SC	5	2500	8/7.5	Belt	230/440	40/30/20	1/3	437,000	8"	37.5"	29"	44.5"	605
14-530	SS-SL-SC	5	3000	10	Belt	230	50	1	437,000	8"	37.5"	29"	44.5"	655

SS FEATURES (not shown on breakout);

- Well Balanced for Easy Maneuverability
- Powder Coated Automotive Quality Finish
- Rear Wheel Locking Brake System
- Built-In Hose Reel Socket
- Heavy Duty Electrical Cord & Hose Storage
- Built-In Gun Cup

Notes:

- · Stainless Steel Belt Guard
- Heavy Duty Electro Plated Fittings
- Exclusive High Strength Plastic Manifold
- Quick Couple Plumbing Connections
- Heavy Duty Rotary Power Switch
- Heating Coil: ASTM A53 Schedule 80 Pipe

- Quick Coil Access
- Fuel Oil Solenoid
- Water Separating Fuel Filter
- In-Line Fuel Shutoff
- Trigger Gun Control w/ 36" Insulated Wand
- 0°, 15°, 25°, & 40° Quick Coupled Nozzles
- 3/8" x 50' High Pressure Hose w/Safety Hose Guards
- Flexible Vinyl Poly Coated Tri-Lingual Decals
- ETL and CETL Listed to UL Std.1776 & CSA Std. B140.11 (Except 40 & 50 Amp Single Phase Models in Standard Form)

SC - all the SS plus:

Configured for you by

ISTRIBUTOR

Clutch Drive System



A Closer Look at the Features:

