



Self Contained Pressure Washer

The **47-Series** is designed to be operated by a single diesel fuel source and utilizes dual clutch driven pumps that allow 10 gallons of hot water at 3000 PSI. This product is capable of operating in three configurations, a single gun 10 GPM at 3000 PSI pressure washer, two gun 5 GPM at 3000 PSI pressure washer or a single gun 5 GPM at 3000 PSI pressure washer.

| GPM at 3000 PSI pressure washer. SPECIFICATIONS | | | | | | | | | | | | | | | |
|---|---|---------------------------------------|--|-------|--|---|-----------------|--|---|---|-------------------------------|--|---|---------------------------|--|
| | | | ENGINE/BURNER SYSTEM | | | | | | DIMENSIONS/WEIGHT | | | | | | |
| Model | GPM | PSI | HP | Drive | Volt | Engine | Engine Start | Fuel Engine/Bur | BT ner | U | L | W | н | LBS. | |
| 47-1028GLDD | | 2800 | 24.8 | Belt | 120 | Kubota | Electric | Diesel/Diesel | 860, | ,000 | 53" | 43" | 50 1/2" | 1550 | |
| Heavy Duty Insulated Cabinet Frame Forklift Pockets for Safe Easy Maneuvering Removable Access Panels Recessed Control Panel Dual Adjustable Temp. Controls Diagnostic Controls Dual Output Connectors Amp Meter | | | | | Murphy Switch Control System Electric Start Shock Absorbing Engine Base Plastic Battery Box Dual Pumps Triplex Ceramic Plunger Pumps Dual Pressure Relief Valves Thermal Pump Protection Dual Horizontal Fuel Efficient Combustion Chambers | | | | Schedule 80 Steel Heating Coils High Efficiency Beckett Pressure Atomized Burners Automatic Electric Burner Ignition Water Separating Fuel Filters Trigger Gun Control (2) 3/8" x 50' High Pressure Hose Assemblies (2) Adjustable Dual Lance Wands Quick Couple Stainless Steel Nozzles | | | | | | |
| A Close | A Closer Look at the Features: | | | | | | | | | | | | | | |
| Ald trac main for your ease of for your ease of For For For For For For For For For For | al Gun 🛩 tlets nt mounted easy access. | C | | | Adda ,1-800 33 | | | | | на 1.4400 1.4400 1.44 | 1922 | Con & y StainI Cham & Powe Si Heats w & mor | High fficiency Burners serves fuel our dollars. ess Steel ber Cover dercoated de Panels Maintenance Exclusive Coil Design nater quicker e efficiently. Forklift Pockets Provides for safe & easy movement. | free, durable protection. | |
| Generator Enables your use of a 110V burner. | | Ol Clutch Save me engthening | otional Drive oney by the life r pump. | 6 | maii costs du | trength Lower htenance le to long turability. | Prevents | sure Relief Valve injury & cost ie to an over- rized system. | | extra la fuel tar operati | arge 40 nk to p ion dur | Gallor rovide ation. | uipped w n 1/8" Ste a longer | | |
| Notes: | | | | | | | | (| Config | gure | d to | r yo | u by | | |
| | | | | | | | | | DIS | sti | RI | BL | E L J T(| DR | |