HOT WATER ELECTRIC DIRECT/BELT DRIVE

ACS-215-EHW



0

1500 PSI @ 2.0 GPM

Fan-Cooled electric motor with manual thermal overload protection







Pump

- Direct or Belt triplex General or Mi-TM pump with ceramic plunger
- Stainless-steel and brass unloader valve
- Thermal Relief Valve
- High pressure detergent injection

Motor

- Totally enclosed fan-cooled electric motor with manual thermal overload protection
- 35-foot power cord with in-line GFCI which meets required CSA Certification
- Solid state electronic ignition

Frame

- Reinforced powder coated steel tube frame
- Powder coated steel hose reel mounting bracket
- Electric cord hanger
- Powder coated steel gun/wand holder
- Four pneumatic tires with locking tire brake

Components

- Energy-efficient top-fired heat exchanger
- Fuel filter/water separator ensures clean fuel supply
- Pressure and high limit safety controls
- No. 1 or No. 2 diesel or kerosene fired burner (Bio-fuel not approved at this time)
- Polyethylene burner fuel tank.
- Easy coil drain helps prevent freezing in cold weather

Unit Includes

- Quick connect nozzles: 0°, 15°, 25° and 40°
- 50-foot x 3/8 inch steel wire-braided pressure hose with quick connects, swivel and bend restrictors
- Insulated trigger gun with safety lock-off
- Adjustable pressure insulated dual lance
- Weight 291 lbs.
- Length 43" x Width 29.5" X Height 36.5"

10-22-1



2361 South Plaza Drive Rapid City, SD 57702 605-341-5154 | 800-666-3664 | Fax: 605-341-4843 Visit our web site at: www.pressureservices.com