HOT HIGH PRESSURE WASHER

Portable · Electric Powered · Diesel Fired

ACS-423-EHWC



4.0 GPM @ 2300 PSI

Model#	GPM	PSI	Pump	Engine	H.P.	Volts	Burner
ACS 2423C	4	2300	General	Baldor	6	230	12VDC Beckett

Standard Features:

- · 1 Phase, 30 amp
- Bypass Cooling
- Stainless Lid & Heat Shield
- SS Float Tank
- Clutch Driven Pump
 GFCI
- GFCI
- 50' of High Pressure Hose
- Mag Wheels & Flat Free Tires
- Hose & gun holder
- Racor Water Separating Fuel Filter
- Hose Reel Receiver
- Rugged 1-1/4" Square Tubing
- Max Output Temperature: 210°
- Heat Rise Degrees Fahrenheit: 155
- Cleaning Comparison Index: 18119
- Input BTU's : 384,000
- Fuel Consumption (GPH): 1.65
- Burner Fuel Tank Capacity: 11
- Approximate Weight (LBS): 595
- · Dimensions 32"W x 48"L x 43"H

Hose Reel Sold Separately

Part Number 18/ACS-SWVL-SE38X150

NOTICE

Bio-Fuel Compatible <u>up to 5%</u> <u>**DO NOT**</u> use a Fuel Blend exceeding 5% Fuel Blend in excess of 5% may result In <u>Burner</u> <u>Failure</u>.

02-03-22

<u>Cleaning Comparison Index</u>- This index is used in the comparison of presure washing equipment by taking into

account the cleaning effects of water pressure, flow, and temperature on cleaning time. The Larger the cleaning comparision idex, the faster the pressure washer will clean.

Fuel Consumption considers an operating duty cycle of 60%.





2361 South Plaza Drive Rapid City, SD 57702 Phone: 605-341-5154 | Fax: 605-341-4843 Contact us at: Sales@PressureServices.com Visit our web site at: www.pressureservices.com