HOT WATER GASOLINE DIRECT DRIVE

ACS-2930-GHW



3000 PSI @ 2.9 GPM 270cc Honda OHV Engine





Pump

- Direct drive triplex piston AR Pump
- Stainless-steel brass unloader valve
- Thermal relief valve
- Low pressure detergent injection

Engine

 Performance-proven Honda OHV engine with low-oil protection and recoil start

Frame

- Reinforced powder coated steel tube frame
- Powder coated steel hose reel mounting bracket
- Wand holder
- Four Flat Free Tires
- Locking tire brake

Components

- Fuel filter/water separator ensure clean fuel supply
- Pressure and high limit controls
- No. 1 or No. 2 diesel or kerosene fired burner (Biofuel not approved at this time)
- Patented Electro Magnetic Firing (EMF) System
- On/Off burner switch
- Maximum Outlet Temperature 200°F

Unit Includes:

- 50-foot x 3/8 inch steel wire-braided pressure hose with screw connects, swivel and bend restrictors.
- Insulated trigger gun with safety lock-off
- Adjustable pressure dual lance with 15-degree fixed and detergent nozzle
- Weight: 407 lbs.
- Length 43" x Width 30" x Height 41"

02-03-22



2361 South Plaza Drive Rapid City, SD 57702 Phone: 605-341-5154 | Fax: 605-341-4843 Contact us at: Sales@PressureServices.com Visit our web site at: www.pressureservices.com