HOT WATER GASOLINE DIRECT DRIVE

ACS-2625-GHW



2500 PSI @ 2.6 GPM 196CC Honda OHV



Pump

- Direct drive triplex piston Mi-T-M pump with ceramic plungers
- · Stainless-steel and brass unloader valve
- Thermal relief valve
- External bypass systems
- Low pressure detergent injection

Engine

 Performance-proven Honda OHV engine with low-oil protection and recoil start

Frame

- Reinforced powder coated steel tube frame
- Wand holder
- Four Flat Free Tires with locking tire brake

Components

- Fuel filter/water separator ensures clean fuel supply
- On/Off burner switch
- Pressure and high limit safety controls
- No. 1 or No. 2 diesel or kerosene fired burner (Bio-fuel no approved at this time.)
- Energy efficient top fired powder coated heat exchanger

Unit Includes:

- Quick connect nozzles (0°, 15°, 25°, 40°)
- 50-foot x 3/8 steel wire-braided pressure hose with quick connects, swivel and bend restrictors.
- Insulated trigger gun with safety lock-off
- Adjustable pressure insulated dual lance
- Weight 295 lbs.
- Length 43" x Width 29.5" x Height 36.5"

02-03-22



2361 South Plaza Drive Rapid City, SD 57702 Phone: 605-341-5154 | Fax: 605-341-4843 Contact us at: Sales@PressureServices.com Visit our web site at: www.pressureservices.com