



Premium Series

Dealer Cold Water Pressure Washers

Electric — Stationary — Belt Drive



This stationary pressure washer is constructed of stainless-steel to resist rust and corrosion, making it the perfect solution for wash bays to clean vehicles and equipment. Food and beverage facility owners use it to keep floors and worktables clean and sanitized.

Pump:

Belt drive triplex piston General pump with ceramic plungers | Forged brass manifold | Thermal relief valve | Pump accepts incoming water up to 175°F | Quick connect low pressure detergent injector

Frame:

Stainless-steel cabinet design with removable panel | Four rubber isolators

Motor:

Totally enclosed fan-cooled electric motor with manual thermal overload protection (2000-PSI models) | Open drip-proof electric motor (1000 and 3000-PSI models) | 4-foot power cord with GFCI

Component:

Time delay shutdown

Unit Includes:

Quick connect nozzles - 0°, 15°, 25° and 40° | 50-foot x 3/8-inch non-marking high pressure hose | Adjustable pressure insulated dual lance | Professional-grade insulated trigger gun with safety lock-off



Premium Series

Cold Water – Electric – Stationary – Belt Drive

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	UNLOADER	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
	1000	2.5	2.0 HP, 120V, 1Ø, 18.8A	Factory preset	NEMA 5-20P	29.5x20.5x15in.	222 lb.	172 lb.
	2000	3.9	6.0 HP, 230V, 1Ø, 22.0A	Factory preset	NEMA 6-30P	29.5x20.5x15in.	272 lb.	214 lb.
*	2000	3.9	6.0 HP, 230V, 3Ø, 15.0A	Factory preset	NEMA L15-20P	29.5x20.5x15in.	262 lb.	204 lb.
*	3000	3.5	8.0 HP, 230V, 3Ø, 20.0A	Factory preset	NEMA L15-30P	29.5x20.5x15in.	292 lb.	234 lb.

**460V motors available as options*

Options:

PART NUMBER	DESCRIPTION	FITS MODELS
	Auto start/stop - When trigger gun is released, the timer will turn unit off; when trigger gun is pulled, unit will restart	All models
	460V on 6.0-HP, 3-phase model - For when you have 460V of power available	
	460V on 8.0-HP, 3-phase model - For when you have 460V of power available	3000-PSI models
	Remote box - Adds control box which may be mounted away from unit to control on/off	All models
	Hour meter - Displays the number of hours unit has been in operation	All models
	Additional remotes (up to 3) - Additional remotes that may be added to unit after the first remote is installed	All models

Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
	Stainless-steel wall mounting bracket - Provides a permanent location for your pressure washer in a shop or plant facility	All models
	Powder coated steel wall mounting bracket - Provides a permanent location for your pressure washer in a shop or plant facility	All models
	Powder coated steel floor stand - Provides a permanent location for your pressure washer in a shop or plant facility	All models



NEMA 5-20P,
20-amp plug



NEMA L15-20P,
20-amp plug



NEMA 6-30P,
30-amp plug



NEMA L15-30P,
30-amp plug



Shown with stainless-steel wall
mounting bracket



Powder coated
steel floor stand

WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.