

PURCLEAN™

SPOT-FREE RINSE SYSTEMS

NEWWAVE™
INDUSTRIES

15,000 GPD Spot-Free Rinse System



Features

- ◆ Water Stabilizer (replaces softener)
- ◆ Inlet & Pressure Pump
- ◆ Carbon Tank with Auto Back Flushing Head
- ◆ Multi-Stage Pressure Pump
- ◆ Low Pressure Shut Off
- ◆ Automatic Membrane Flush
- ◆ Production & Reject Meters
- ◆ On Board TDS Meter
- ◆ Two Step Powdercoated Aluminum Frame
- ◆ Repressurization and / or Reject Recapture Pump
- ◆ Thin Film Membrane
- ◆ Hinged Control Box - Quick and Easy Internal Access
- ◆ ETL Listed

Specifications	15,000 GPD Spot Free Rinse System Stand Mount (RO)	
Water Requirements	(2) 1.25" Water line w/ FPT ball valves, 40 GPM at 30 PSI. Mount 4 feet up from floor to the right of the spot free rinse system and (1) drain.	
Electrical Requirements	3Ph	(1) 208/230 or 460/480 20 amp circuit, put circuit 5 feet up from the floor to the right of the spot-free rinse system
RO Output	Production - 10.4 GPM	
Reject	4.2 GPM, 2.1 GPM Out of each reject flow meter	
RO Motor	5 HP booster pump	
RO Motor Amps	3Ph 208/230 = 12.4 amps	3Ph 460/480 = 6.2 amps
Dimensions	36" Wide X 92" Tall X 24" Deep	
Net Weight	1100 Lbs.	
Delivery Pump	Standard delivery pump 15 GPM max at 50 PSI max. Automatic freshwater bypass pressure and GPM varies depending on which car wash application. (Call PurClean for more info.)	