

CLEAN

Alkaline Presoak

DESCRIPTION

This product benefits from the latest surfactant and alkaline builder technology to bring consistent results. Additionally, it has improved hard water tolerance for those sites where consistent soft water is a problem. It also works as a great tire & wheel cleaner or high pressure prep soap. Save on shipping and space when purchasing this as part of the EZ Presoak System.

USAGE INSTRUCTIONS

This product can be applied under low or high pressure. When applied as a presoak it is best applied under low pressure. In a touch free setting apply at 36-64:1 (8-14 drops). Allow to dwell before rinsing. In friction or self-serve applications apply at 75-125:1 (4-7 drops). Product can also be applied as a tire & wheel cleaner. Apply on low pressure through a CTA at 16-25:1 (20-30 drops). For application as a high pressure prep detergent consult your sales representative.

FEATURES

- Tough on window masks
- Versatile crossover application
- 2 Twin Packs = 55-gallons of Presoak
- Great show and performance

SIZES AVAILABLE

5-gallon pails Code: 10-10105-005
15-gallon drums Code: 10-10105-015
30-gallon drums Code: 10-10105-030
55-gallon drums Code: 10-10105-055
EZ Presoak System Code: 10-10105-825

SPECIFICATIONS

COLOR: RED
FRAGRANCE: NONE
FOAM: WHITE
PH: 13-14

Drop Count (Titration)	Oz/Gal of water	Ratio to 1
5	1.25	101
6	1.50	84
7	1.75	72
8	2.00	63
9	2.25	56
10	2.50	50
11	2.75	46
12	3.00	42
13	3.25	38
14	3.50	36
16	4.00	31
18	4.50	27



**ANYTHING
BUT ORDINARY**