

LIFT OFF

Acidic Presoak

DESCRIPTION

This product is a low pH presoak to be used as the first step of a two-step wash process. This aggressive product contains no HF or Ammonium Bifluoride. Instead it uses other acids to effectively remove tough road films and leave paint and glass cleaner and shinier.

USAGE INSTRUCTIONS

This product should be applied as the first step in a two-step cleaning process. For touch free cleaning apply 125-200:1 (6-10 drops). For friction applications start at a rate of 200-325:1 (4-6 drops). For more difficult cleaning conditions slowly increase strength. For additional cleaning and foam reduction, product can be added later in tunnels to wraps. Using soft water will improve foam profile and product performance.

FEATURES

- Contains no HF or ABF
- Increased shine to metal and glass
- Rinses easily
- Keep cloth and bay walls clean


SIZES AVAILABLE

5-gallon pails Code: 10-10085-005
15-gallon drums Code: 10-10085-015
30-gallon drums Code: 10-10085-030
55-gallon drums Code: 10-10085-055

SPECIFICATIONS

COLOR: STRAW
FRAGRANCE: NONE
FOAM: WHITE
PH: 1-2

Drop Count (Titration)	Oz/Gal of water	Ratio to 1
8	.80	159
10	1.0	127
12	1.2	106
14	1.4	90
16	1.6	79
18	1.8	70
20	2.0	63
22	2.2	57
24	2.4	52
26	2.6	48
28	2.8	45
30	3.0	42



**ANYTHING
BUT ORDINARY**