## HOT PRESSURE WASHER GASOLINE DIRECT DRIVE



## Powered by the Reliable 389cc Honda GX390 OHV Engine

## 4000 PSI @ 3.7 GPM

Gas tank Capacity: 1.61 Gallons Burner Fuel Tank Capacity: 10.0 Gallons Dimension: 57.5L x 35.5W x 59.5H Ship WT: 601 Lbs. Net Wt.: 478 Lbs. The new 12V hot water gas pressure washer may be compact, but it is ready to clean the toughest grime.

Standard Features:

- Direct drive triplex piston General pump with ceramic plungers
- Powder Coated Frame and Coil Wrap
- Stainless-steel and brass unloader valve, adjustable
- Forged brass manifold

Thermal relief valve

- 12V electric start with battery included
  - Reinforced powder coated steel tube frame with center balanced lifting hook
- 15-inch pneumatic tires
- Quick connect nozzles: 0°, 15°, 25° and 40°
- Low Pressure Detergent Injector
- Quick connect wet steam nozzle 25°
- 50-foot x 3/8-inch steel wire-braided highpressure hose with quick connects, swivel and bend restrictors
- Adjustable pressure insulated dual lance
- Profession-grade insulated trigger gun with safety lock-off
- 1/2-inch schedule 80 pipe coil with 4-pancake bottom fired heat exchanger 12V Beckett burner
- No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel)



0

2361 South Plaza Drive Rapid City, SD 57702 Phone: 605-341-5154 | Fax: 605-341-4843 Contact us at: Sales@PressureServices.com Visit our web site at: www.pressureservices.com