

OIL FIRED PORTABLE PRESSURE WASHER | Specifications:

GENERAL						ELECTRICAL			BURNER SYSTEM		DIMENSIONS/WEIGHT			
Model	Туре	GPM	PSI	HP	Drive	Volt	Amp	Ph	BTU	Stack	L	W	н	Lb
14-423	SS/SL/SC	4	2300	6/7.5/7.5	Belt/Clutch	230/230/440	30/20/15	1/3/3	275,000	Exchange	48"	33"	44.5"	520
14-430	SS/SL/SC	4	3000	8/7.5/7.5	Belt/Clutch	230/230/440	40/20/15	1/3/3	275,000	Exchange	48"	33"	44.5"	530
14-530	SS/SL/SC	5	3000	10	Belt/Clutch	230	50	1	299,000	Exchange	48"	33"	44.5"	570

SS Features (not shown on breakout):

- · Well Balanced Design for Easy Maneuverability
- · Built-In Gun Cup
- · Stainless Steel Belt Guard
- Heavy Duty Electro Plated Fittings
- · Exclusive High Strength Nylon Manifold
- Quick Couple Plumbing Connections
- · Heavy Duty Rotary Power Switch
- Panel Mount Adjustable Temp. Control
- High Limit Temp. Control
- ASTM A53 Schedule 80 Steel Heating Coil

- Exclusive Heat Chamber Insulation System
- Quick Coil Access
- · Fuel Oil Solenoid
- Water Separating Fuel Filter
- · In-Line Fuel Shutoff
- Trigger Gun Control
- 36" Insulated Wand
- 0°, 15°, 25°, & 40° Quick Coupled Stainless Steel Nozzles
- 3/8" x 50' High Pressure Hose
- Tri-Lingual Decals

SL - Includes All the Features of SS Plus:

- · Time Delay Shutdown
- · Hour Meter
- Magnetic Starter

SC - Includes All the Features of SS Plus:

· Clutch Drive System



Configured for you by:

