

Aluminum Series

Dealer Cold Water Pressure Washers



Industrial cleaning contractors love this powerful and lightweight pressure washer because it delivers high performance on a routine basis. Stains on brickwork and concrete are no match for this mighty machine.

Pump:

Belt drive triplex piston AR or General pump with ceramic plungers | External bypass system allows more water into the system to protect from heat build-up | Stainless-steel and brass trapping unloader

Frame:

Patented vibration isolation plate with four rubber isolators | Lightweight, corrosion-resistant aluminum frame and base plate with 1¼-inch tube handles | Two-piece belt guard for quick access to belts | 13-inch flat-free tires

Unit Includes:

Quick connect nozzles - 0°, 15°, 25° and 40° | External downstream detergent injector with detergent nozzle | 50-foot x %-inch non-marking high pressure hose | 48-inch lance with rubber grip | Professional-grade insulated "easy pull" trigger gun with safety lock-off







Aluminum Series

Cold Water - Gasoline - Portable - Belt Drive

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	PUMP	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
	3500	3.7	389cc Honda GX390 OHV	General	46.5x28x27.5in.	215 lb.	165 lb.
	3500	3.7	429cc Kohler CH440 OHV	General	46.5x28x27.5in.	237 lb.	173 lb.
	3500	3.7	389cc Honda GX390 OHV	AR	46.5x28x27.5in.	215 lb.	165 lb.
	3500	3.7	429cc Kohler CH440 OHV	AR	46.5x28x27.5in.	219 lb.	155 lb.
	4000	3.5	389cc Honda GX390 OHV	General	46.5x28x27.5in.	223 lb.	159 lb.
	4000	3.5	429cc Kohler CH440 OHV	General	46.5x28x27.5in.	219 lb.	173 lb.
	4000	3.5	389cc Honda GX390 OHV	AR	46.5x28x27.5in.	207 lb.	143 lb.
	4000	3.5	429cc Kohler CH440 OHV	AR	46.5x28x27.5in.	215 lb.	155 lb.

Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
	High pressure detergent injector - High pressure water mixes with detergent to clean even the heaviest build-up	All models
	50-ft. x 3/8-in. non-marking high pressure hose - For when you need extra hose for added mobility	All models
	Rotating nozzle - Increase your cleaning power and decrease your cleaning time, 5100-PSI rated, 3.5 orifice	All models

