

CHV Series

WATER TREATMENT SYSTEMS



The tough, high gallon-per-minute centrifugal system blasts away mud and dirt allowing for an easier and less timely workload during the pressure wash cycle. The CHV is the perfect alternative to fire hoses and high volume water cannons. Producing 25 GPM at 500 PSI with a variable spray pattern, the CHV is extremely effective for mud removal and heavy washout application. It is the perfect choice for use with water reclamation systems and for customers who want to lower their water consumption. The industrial diaphragm pump can tolerate silty or reclaimed water.



CHV-0525-0ME3

Typical applications include:

- Rental Yards
- Lumber Yards
- Mining Operations
- Heavy Equipment Dealers
- Solid Waste Haulers

MODEL NUMBER	DESCRIPTION	GPM @ PSI	HORSEPOWER	DIMENSIONS (LxWxH)	SHIP WT.
CHV-0525-0ME1	Cold water stationary electric belt driven pressure washer, 230V, 1Ø, 41.5A	25 @ 500	10.0	38in.x23.5in.x24in.	432 lb.
CHV-0525-0ME3	Cold water stationary electric belt driven pressure washer, 230V, 3Ø, 25.6A	25 @ 500	10.0	38in.x23.5in.x24in.	407 lb.

CHV Series ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
16-0440	Replacement gun - Replacement high volume long range gun with adjustable pattern from straight stream to cone mist	All models
50-0185	Accessory hose reel - Add a hose reel for convenient storage of your hose; holds up to 200-feet of ¾-inch hose	All models

CHV Series OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
CX-0072	300-gallon tank - 300-gallon tank with stand, suction hose and float included	All models
CX-0073	460V, 3-phase - For when you have 460V of power available	All models
CX-0074	18-in. stand - Raises unit off of ground	All models
CX-0075	Remote box- For when unit is not near spraying location	All models