



# Premium Series

## Dealer Cold Water Pressure Washers

Electric — Portable — Belt Drive



Shown with 460V, 3-phase motor option

*With up to 5000-PSI of cleaning power, this series of pressure washers is perfect for cleaning heavily soiled equipment, greasy floors and dirty concrete walls.*

#### Pump:

Belt drive triplex piston General pump with ceramic plungers | External bypass system allows more water into the system to protect from heat build-up | Forged brass manifold | Thermal relief valve | Water filter with clear sleeve for screen inspection

#### Frame:

Powder coated steel frame and base plate with 1¼-inch tube handles | Totally enclosed powder coated steel belt guard | 13-inch flat-free tires

#### Motor:

Totally enclosed fan-cooled electric motor with thermal overload protection | 10-foot power cord

#### Component:

Heavy-duty dual cogged belt drive system

#### Unit Includes:

Quick connect nozzles - 0°, 15°, 25° and 40° | 50-foot x ¾-inch non-marking high pressure hose | 36-inch lance with rubber grip (48-inch on 4000 and 5000-PSI models) | Professional-grade insulated trigger gun with safety lock-off



# Premium Series

## Cold Water – Electric – Portable – Belt Drive

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	UNLOADER	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
	2400	4.6	7.5 HP, 230V, 1Ø, 32.0A	Factory preset	NEMA 6-50P	46x28x30in.	345 lb.	333 lb.
*	2400	4.6	8.0 HP, 230V, 3Ø, 20.0A or 8.0 HP, 460V, 3Ø, 10.0A	Factory preset	NEMA L15-30P	45.5x32.5x30in.	355 lb.	343 lb.
	3000	3.5	7.5 HP, 230V, 1Ø, 32.0A	Factory preset	NEMA 6-50P	46x28x30in.	350 lb.	338 lb.
*	3000	3.5	8.0 HP, 230V, 3Ø, 20.0A or 8.0 HP, 460V, 3Ø, 10.0A	Factory preset	NEMA L15-30P	45.5x32.5x30in.	403 lb.	301 lb.
	3000	4.8	10.0 HP, 230V 1Ø, 41.5A	Factory preset	NEMA 6-50P	45.5x32.5x30in.	470 lb.	396 lb.
*	3000	4.8	10.0 HP, 230V, 3Ø, 26.0A or 10.0 HP, 460V, 3Ø, 13.0A	Factory preset	NEMA L15-50P	45.5x32.5x30in.	450 lb.	376 lb.
*	4000	3.9	15.0 HP, 230V, 3Ø, 40.0A or 15.0 HP, 460V, 3Ø, 20.0A	Factory preset	NEMA L15-50P	45.5x32.5x30in.	505 lb.	431 lb.
*	5000	4.0	15.0 HP, 230V, 3Ø, 40.0A or 15.0 HP, 460V, 3Ø, 20.0A	Factory preset	NEMA L15-50P	45.5x32.5x30in.	505 lb.	431 lb.

\*460V motors available as options

### Options:

PART NUMBER	DESCRIPTION	FITS MODELS
	460V on 8.0-HP, 3-phase models - For when you have 460V of power available	
	36-in. insulated dual lance - Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	2400 & 3000-PSI models
	460V on 15.0-HP, 3-phase models - For when you have 460V of power available	4000 & 5000-PSI models
	460V on 10.0-HP, 3-phase models - For when you have 460V of power available	
	Stationary option - This option will remove the existing tall handle and wheels, which will be replaced with a short handle and rubber feet for stationary applications	
	Stationary option - This option will remove the existing tall handle and wheels, which will be replaced with a short handle and rubber feet for stationary applications	

### Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
	High pressure detergent injector - High pressure water mixes with detergent to clean even the heaviest build-up	All models
	50-ft. x 3/8-in. non-marking high pressure hose - For when you need extra hose for added mobility	5000-PSI models
	50-ft. x 3/8-in. non-marking high pressure hose - For when you need extra hose for added mobility	2400 to 4000-PSI models
	Low pressure detergent injector - Allows the user to apply the recommended detergents	All models



NEMA 6-50P,  
50-amp plug



NEMA L15-30P,  
30-amp plug



NEMA 15-50P,  
50-amp plug



**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).