



# Skid Gasoline/Diesel

## Dealer Hot Water Pressure Washers

### HDB Series — Belt Drive



Shown with wheel kit option

*Perfect for agriculture and construction applications where mobility is a must, these compact skids are extremely portable and can fit through a 30-inch doorway. The versatility of this series makes it a popular choice for several industries.*

#### Pump:

Belt drive triplex piston General pump with ceramic plungers | Low pressure detergent injector

#### Engine:

Performance-proven gasoline engine or Kohler diesel engine with electric start – battery not included

#### Frame:

Powder coated steel square tube skid frame | Stainless-steel removable front panel | Optional wheel kit with locking tire brake, four tires and solid steel threaded axles

#### Components:

Stainless-steel coil wrap heat exchanger with horizontal schedule 80 pipe coil | 12V Beckett burner – no need for a generator – battery not included | No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel) | Adjustable thermostat

#### Miscellaneous:

Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

#### Unit Includes:

Quick connect nozzles - 0°, 15°, 25° and 40° | 50-foot x 3/8-inch high pressure hose | Adjustable pressure insulated dual lance | Professional-grade insulated trigger gun with safety lock-off



# Skid Gasoline/Diesel

## Hot Water – HDB Series – Belt Drive

### Gasoline Models

MODEL NUMBER	PSI	GPM	DISPLACEMENT/ENGINE	ENGINE FUEL TANK CAPACITY	BURNER FUEL TANK CAPACITY	BURNER FUEL CONSUMPTION	BTU per hour	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
3000	3.9	3.9	389cc Honda GX390 OHV	1.7 gallons	10.0 gallons	2.45 gph	343,000	53.5x28.75x42in.	685 lb.	566 lb.
3000	4.8	4.8	480cc Vanguard OHV	10.0 gallons	10.0 gallons	2.76 gph	386,400	53.5x28.75x42in.	720 lb.	601 lb.
3000	4.8	4.8	624cc Kohler CH620 OHV	10.0 gallons	10.0 gallons	2.76 gph	386,400	53.5x28.75x42in.	736 lb.	617 lb.

### Diesel Model

MODEL NUMBER	PSI	GPM	HORSEPOWER/ENGINE	ENGINE FUEL TANK CAPACITY	BURNER FUEL TANK CAPACITY	BURNER FUEL CONSUMPTION	BTU per hour	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
3000	3.9	3.9	9.1 HP Kohler KD440 OHV	1.3 gallons	10.0 gallons	2.45 gph	343,000	53.5x28.75x42in.	745 lb.	626 lb.

### Options:

PART NUMBER	DESCRIPTION	FITS MODELS
	<b>Hour meter</b> - Displays the number of hours unit has been in operation	All models
	<b>Steam</b> - Increases outlet temperature to 250°F	Honda models
	<b>High pressure chemical (K7)</b> - Adjustable high pressure chemical, includes float tank	All models
*	<b>High pressure chemical (trapping unloader)</b> - Adjustable high pressure chemical, includes float tank	All models
	<b>Panel engine key switch</b> - Moves engine key switch from engine to front panel	Vanguard models
	<b>Steam</b> - Increases outlet temperature to 250°F, includes steam nozzle and valve	Vanguard and Kohler models
	<b>Trapping unloader</b> - For hose runs longer than 50-feet and for cleaning elevated areas	All models
	<b>Three-way ball valve</b> - Allows the pressure washer to be operated from garden hose, float tank, or trailer supply by adjusting ball lever valve	All models

**\*Trapping unloader is required when ordering the high pressure chemical option.**

### Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
	<b>Stack adapter</b> - Allows 8-inch flue pipe to be installed to boiler exhaust port	All models
	<b>Gasket (for stack adapter)</b> - Seals between stack adapter and boiler housing	All models
	<b>Wheel kit</b> - 4 rubber wheels allows unit to become portable	All models
	<b>Caster wheel kit</b> - Includes 2 caster wheels and 2 rubber wheels for easier movement on flat surfaces	All models
	<b>Hot water skid equipment cover</b> - Keeps your equipment clean, dry and looking like new, made from 600-denier vinyl-backed polyester, water resistant, drawstrings to secure cover	All models



**WARNING:** Cancer and Reproductive Harm - [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).