



Stationary Natural Gas/LP Dealer Hot Water Pressure Washers

HEG High Volume Wash Series — Belt Drive



Even the most demanding cleaning jobs are no match for the super-efficient, high volume HEG series. Designed to tackle heavy soil and solid dirt, oil and even the worst grease, choose from either a 2000 or 3000 PSI model.

Pump:

Belt drive triplex piston General pump with ceramic plungers

Motor:

Open drip-proof electric motor with manual thermal overload protection

Frame:

Powder coated steel frame and removable side panels

Components:

½-inch schedule 80 pipe coil with 8-pancake heat exchanger (¾-inch on 2000-PSI models) | Natural gas or LP gas-fired (vapor only) natural draft with aspirating-type burner, 12-inch stack | Electronic ignition with intermittent pilot | Adjustable outlet thermostat for main temperature control | Polyethylene float tank (8-gallon with in-line screen filter) | Time delay shutdown

Miscellaneous:

Unique coil design allows thermostat to sense upstream water temperature to regulate outlet temperatures preventing large temperature swings | Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

Unit Includes:

Quick connect nozzles - 0°, 15°, 25° and 40° and fixed detergent nozzle | 50-foot x ⅜-inch steel wire-braided high pressure hose (½-inch on 2000-PSI models) | Adjustable pressure insulated dual lance | Professional-grade insulated trigger gun with safety lock-off



Stationary Natural Gas/LP

Hot Water – HEG High Volume Wash Series – Belt Drive

| MODEL NUMBER | PSI | GPM | HORSEPOWER/MOTOR | NATURAL GAS BTU per hour | LP GAS BTU per hour | DIMENSIONS (LxWxH) | SHIP WT. | NET WT. |
|--------------|-----|------|--------------------------|--------------------------|---------------------|---------------------|----------|----------|
| 2000 | 9.9 | 15.0 | 15.0 HP, 230V, 3Ø, 40.6A | 768,000 | 730,000 | 78.5x34.75x65.75in. | 1570 lb. | 1420 lb. |
| 2000 | 9.9 | 15.0 | 15.0 HP, 460V, 3Ø, 20.3A | 768,000 | 730,000 | 78.5x34.75x65.75in. | 1570 lb. | 1420 lb. |
| 2000 | 9.9 | 15.0 | 15.0 HP, 575V, 3Ø, 16.2A | 768,000 | 730,000 | 78.5x34.75x65.75in. | 1539 lb. | 1389 lb. |
| 2000 | 9.9 | 15.0 | 15.0 HP, 208V, 3Ø, 44.0A | 768,000 | 730,000 | 78.5x34.75x65.75in. | 1553 lb. | 1403 lb. |
| 3000 | 7.8 | 15.0 | 15.0 HP, 230V, 3Ø, 40.6A | 650,000 | 619,500 | 70x34.75x54.5in. | 1207 lb. | 1057 lb. |
| 3000 | 7.8 | 15.0 | 15.0 HP, 460V, 3Ø, 20.3A | 650,000 | 619,500 | 70x34.75x54.5in. | 1207 lb. | 1057 lb. |
| 3000 | 7.8 | 15.0 | 15.0 HP, 575V, 3Ø, 16.2A | 650,000 | 619,500 | 70x34.75x54.5in. | 1176 lb. | 1026 lb. |
| 3000 | 7.8 | 15.0 | 15.0 HP, 208V, 3Ø, 44.0A | 650,000 | 619,500 | 70x34.75x54.5in. | 1190 lb. | 1040 lb. |

Options:

| PART NUMBER | DESCRIPTION | FITS MODELS |
|-------------|--|-----------------|
| | Liquid propane (vapor only) - Converts natural gas pressure washer to operate on liquid propane (vapor only) | 3000-PSI models |
| | Auto start/stop - When trigger gun is released timer will turn unit off; when trigger gun is pulled, unit will restart | All models |
| * | 1 Remote station - Adds control box which may be mounted away from unit to control on/off, burner and soap injection | All models |
| | Additional remotes (up to 3) - Additional remotes that may be added to the unit after the first remote is installed | All models |
| | Stainless-steel access panels - Converts powder coated painted access panels to stainless-steel material | 3000-PSI models |
| | Stainless-steel coil wrap - Converts powder coated painted coil wrap to stainless-steel material | 3000-PSI models |
| | Liquid propane (vapor only) - Converts natural gas pressure washer to operate on liquid propane (vapor only) | 2000-PSI models |
| | Stainless-steel access panels - Converts powder coated painted access panels to stainless-steel material | 2000-PSI models |
| | Stainless-steel coil wrap - Converts powder coated painted coil wrap to stainless-steel material | 2000-PSI models |
| | Balanced temperature control - Thermostat in heating coil anticipates spiking temperature and cycles the burner to maintain steady outlet temperatures | 3000-PSI models |
| | Balanced temperature control - Thermostat in heating coil anticipates spiking temperature and cycles the burner to maintain steady outlet temperatures | 2000-PSI models |
| | Dual gun - Two guns may be sprayed at the same time, flow is divided between the two guns while each operator maintains equal system pressure; includes balanced temperature control option | 3000-PSI models |
| | Dual gun - Two guns may be sprayed at the same time, flow is divided between the two guns while each operator maintains equal system pressure; includes balanced temperature control option | 2000-PSI models |

Accessory:

| PART NUMBER | DESCRIPTION | FITS MODELS |
|-------------|---|-------------|
| | Drafter diverter, 12-inch - For use during installation. Prevents backdrafts through the flue. | All models |

INSTALLATION RECOMMENDATION:

This pressure washer must have a clearance of 2-feet on all sides and 4-feet above the unit.

Gas Supply Line:

Natural Gas

7 to 8-inch water column input

LP Gas

12 to 14-inch water column input

Recommended Pipe Sizes for Gas Supply Line:

| | Distance to Unit from Regulator | | |
|-----------------------|---------------------------------|---------------------|----------------------|
| | 0-feet to 50-feet | 50-feet to 100-feet | 100-feet to 200-feet |
| Natural Gas pipe size | 1½-inch IPS | 2-inch IPS | 2½-inch IPS |
| LP Gas pipe size | 1½-inch IPS | 1½-inch IPS | 1¾-inch IPS |



Optional Remote Station