



# Stationary Oil-Fired

## Dealer Hot Water Pressure Washers

### HEO Series — Belt Drive



Shown with fuel tanks option

*Designed as a stationary unit with removable side panels, this efficient hot water pressure washer is the perfect solution if you are looking for a wash bay system. The powder coated steel frame makes it extremely durable under tough conditions.*

#### Pump:

Belt drive triplex piston General pump with ceramic plungers | Thermal relief valve | Adjustable high pressure detergent injector

#### Motor:

Open drip-proof electric motor with manual thermal overload protection

#### Frame:

Powder coated steel frame and removable side panels

#### Components:

1/2-inch schedule 80 pipe coil with 5-pancake heat exchanger | 10-inch draft diverter | On/Off burner, pump and motor switches | Pressure switch and over-pressure safety controls | 24V control system | Polyethylene float tank (4-gallon with in-line screen filter) | Adjustable thermostat

#### Miscellaneous:

Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F (250°F/121°C outlet temperature with steam option) | Designed to run on an existing fuel tank (Optional fuel tanks available)

#### Unit Includes:

Quick connect nozzles - 0°, 15°, 25° and 40° and fixed detergent nozzle | 50-foot x 3/8-inch steel wire-braided high pressure hose | Adjustable pressure insulated dual lance | Professional-grade insulated trigger gun with safety lock-off



# Stationary Oil-Fired Hot Water – HEO Series – Belt Drive

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	BTU per hour	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
	2000	4.2	6.0 HP, 230V, 1Ø, 27.1A	386,400	56.5x29x49.75in.	844 lb.	724 lb.
	2000	4.2	6.0 HP, 230V, 3Ø, 17.6A	386,400	56.5x29x49.75in.	844 lb.	724 lb.
	2000	4.2	6.0 HP, 460V, 3Ø, 8.8A	386,400	56.5x29x49.75in.	844 lb.	724 lb.
	2000	4.2	6.0 HP, 208V, 1Ø, 29.8A	386,400	56.5x29x49.75in.	844 lb.	724 lb.
	2000	4.2	6.0 HP, 208V, 3Ø, 20.1A	386,400	56.5x29x49.75in.	844 lb.	724 lb.
	3000	3.9	8.0 HP, 230V, 1Ø, 38.6A	343,000	56.5x29x49.75in.	878 lb.	758 lb.
	3000	3.9	8.0 HP, 230V, 3Ø, 21.6A	343,000	56.5x29x49.75in.	878 lb.	758 lb.
	3000	3.9	8.0 HP, 460V, 3Ø, 10.8A	343,000	56.5x29x49.75in.	878 lb.	758 lb.
	3000	3.9	8.0 HP, 208V, 1Ø, 42.1A	343,000	56.5x29x49.75in.	878 lb.	758 lb.
	3000	3.9	8.0 HP, 208V, 3Ø, 24.6A	343,000	56.5x29x49.75in.	878 lb.	758 lb.
	3000	4.8	10.0 HP, 230V, 1Ø, 45.6A	428,400	56.5x29x49.75in.	878 lb.	758 lb.
	3000	4.8	10.0 HP, 230V, 3Ø, 26.6A	428,400	56.5x29x49.75in.	878 lb.	758 lb.
	3000	4.8	10.0 HP, 460V, 3Ø, 13.3A	428,400	56.5x29x49.75in.	878 lb.	758 lb.
	3000	4.8	10.0 HP, 208V, 1Ø, 50.3A	428,400	56.5x29x49.75in.	878 lb.	758 lb.
	3000	4.8	10.0 HP, 208V, 3Ø, 30.6A	428,400	56.5x29x49.75in.	878 lb.	758 lb.

## Options:

PART NUMBER	DESCRIPTION	FITS MODELS
	<b>K7 unloader; flow activated (auto start/stop N/A)</b> - Converts pressure trapping unloader system to flow actuated K7 unloader	
	<b>Hour meter</b> - Displays the number of hours unit has been in operation	All models
*	<b>Time delay shutdown</b> - Timer will shut unit off automatically when trigger gun is released and timer reaches setting	All models
*	<b>Remote station (auto start/stop N/A)</b> - Adds control box which may be mounted away from unit to control on/off, burner and soap injection	All models
	<b>Additional remotes (up to 3)</b> - Additional remotes that may be added to the unit after the first remote is installed	All models
	<b>Auto start/stop</b> - When trigger gun is released timer will turn unit off; when trigger gun is pulled, unit will restart	All models
	<b>K7 unloader; flow activated (auto start/stop N/A)</b> - Converts pressure trapping unloader system to flow actuated K7 unloader	
	<b>Dual gun</b> - Two guns may be sprayed at the same time, flow is divided between the two guns while each operator maintains equal system pressure	
	<b>Stainless-steel access panels</b> - Converts powder coated painted access panels to stainless-steel material	All models
	<b>Stainless-steel coil wrap</b> - Converts powder coated painted coil wrap to stainless-steel material	All models
	<b>Painted box kit</b> - Adds painted side and end panels	All models
	<b>Painted and stainless-steel box kit</b> - Adds stainless-steel side panels and painted end panels	All models
	<b>250°F steam</b> - Steam option adjusts unloader valve counter-clockwise increasing outlet temperature to 250°F while lowering system pressure	2000-PSI models
	<b>250°F steam</b> - Steam option adjusts unloader valve counter-clockwise increasing outlet temperature to 250°F while lowering system pressure	
	<b>250°F steam</b> - Steam option adjusts unloader valve counter-clockwise increasing outlet temperature to 250°F while lowering system pressure	
	<b>Auto start/stop and first remote</b> - When trigger gun is released timer will turn unit off; when trigger gun is pulled, unit will restart; adds control box which may be mounted away from unit to control on/off, burner and soap injection	All models
	<b>Elevated float tank, 4.0 GPM</b> - Float tank is located at the back of the unit	
	<b>Elevated float tank, 5.0 GPM</b> - Float tank is located at the back of the unit	
^	<b>(2) 10-gallon fuel tanks</b> - Adds 20-gallon fuel capacity to unit versus hose hook-up to fuel supply	All models
*	<b>Time delay shutdown and first remote</b> - Timer will shut off automatically when trigger gun is released and timer reaches setting; adds control box which may be mounted away from unit to control on/off, burner and soap injection	All models

**\*You cannot order time delay shutdown and remote station together, you will need to order time delay shutdown and first remote instead. See photo of remote station below.**

**^ You must also order option elevated float tank (4.0 or 5.0 GPM) when ordering (2) 10-gallon fuel tanks.**



**\*Optional Remote Station**



Shown with panels removed

**⚠ WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.**