

Portable Electric

Dealer Hot Water Pressure Washers







Designed for heavy-duty industrial cleaning jobs requiring hot water, the belt-driven HHB Series can easily handle demanding jobs. It is a popular choice on construction jobsites, agricultural locations and for indoor commercial cleaning applications.

Pump:

Belt drive triplex piston AR or General pump with ceramic plungers Adjustable high pressure detergent injector

Motor:

Open drip-proof electric motor with manual thermal overload protection 35-foot power cord

Frame:

Wrinkle-finish powder coated steel frame assembly | 13-inch flat-free tires with rear tire brake

Components:

Stainless-steel coil wrap heat exchanger with horizontal schedule 80 pipe coil | No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel) | Racor fuel filter/water separator | Adjustable thermostat | Polyethylene float tank with inlet filter screen | 10-gallon polyethylene fuel tank

Miscellaneous:

Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

Unit Includes:

Quick connect nozzles - 0°, 15°, 25° and 40° and low pressure nozzle (except on 300-PSI model) | 50-foot x %-inch high pressure hose (50-foot steam hose on 300-PSI model) | Adjustable pressure insulated dual lance (except on 300-PSI model) | Single lance with dual insulated grips; steam nozzle (300-PSI model) | Professional-grade insulated trigger gun with safety lock-off



Portable Electric

Hot Water - HHB Series - Belt Drive

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	PLUG TYPE	BURNER FUEL TANK CAPACITY	BURNER FUEL CONSUMPTION	BTU per hour	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
	1000	2.0	1.5 HP, 115V, 1Ø, 16.2A	AR	NEMA 5-20P	10.0 gallons	1.23 gph	172,200	57x30x41.5in.	606 lb.	486 lb.
	1000	2.8	2.0 HP, 115V, 1Ø, 20.0A	AR	NEMA 5-20P	10.0 gallons	1.84 gph	257,600	57x30x41.5in.	610 lb.	490 lb.
	1500	1.8	2.0 HP, 115V, 1Ø, 19.9A	AR	NEMA 5-20P	10.0 gallons	1.23 gph	172,200	57x30x41.5in.	610 lb.	490 lb.
	2000	4.2	6.0 HP, 230V, 1Ø, 28.0A	General	NEMA 6-30P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	670 lb.	550 lb.
	2500	2.8	6.0 HP, 230V, 1Ø, 28.0A	AR	NEMA 6-30P	10.0 gallons	1.84 gph	257,600	57x30x41.5in.	650 lb.	540 lb.
*	300	2.5	1.5 HP, 115V, 1Ø, 12.5A	AR	NEMA 5-15P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	480 lb.	460 lb.

*Steam unit







NEMA 5-15P, 15-amp plug

NEMA 5-20F 20-amp plud

NEMA 6-30F 30-amp plug

