



# Portable Electric

## Dealer Hot Water Pressure Washers

### HHS Series — Belt Drive



*Completely portable, the HHS Series is easy to use and one of the most reliable in the industry. It can easily tackle the toughest cleaning jobs including grease, grime and stubborn stains.*

#### Pump:

Belt drive triplex piston AR or General pump with ceramic plungers | Adjustable high pressure detergent injector

#### Motor:

Open drip-proof electric motor with manual thermal overload protection | 35-foot power cord

#### Frame

Wrinkle-finish powder coated steel frame assembly | 13-inch flat-free tires with rear tire brake

#### Components:

Stainless-steel coil wrap heat exchanger with horizontal schedule 80 pipe coil | No. 1 or No. 2 fuel oil, diesel or kerosene fired burner (Not approved for bio-fuel) | Auto start/stop | Time delay shutdown | Hour meter | Racor fuel filter/water separator | Adjustable thermostat | Polyethylene float tank with inlet filter screen | 10-gallon polyethylene fuel tank

#### Miscellaneous:

Temperature rise 150°F/66°C above ambient, maximum outlet temperature is 200°F

#### Unit Includes:

Quick connect nozzles - 0°, 15°, 25° and 40° and low pressure nozzle | 50-foot x 3/8-inch high pressure hose | Adjustable pressure insulated dual lance | Professional-grade insulated trigger gun with safety lock-off



All models except

# Portable Electric

## Hot Water – HHS Series – Belt Drive

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	PLUG TYPE	BURNER FUEL TANK CAPACITY	FUEL CONSUMPTION	BTU per hour	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
1000	2.8	2.0	2.0 HP, 115V, 1Ø, 20.0A	General	NEMA 5-20P	10.0 gallons	1.84 gph	257,600	57x30x41.5in.	610 lb.	490 lb.
2000	4.2	6.0	6.0 HP, 230V, 1Ø, 28.0A	AR	NEMA 6-30P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	670 lb.	550 lb.
2000	4.2	6.0	6.0 HP, 230V, 1Ø, 28.0A	General	NEMA 6-30P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	670 lb.	550 lb.
2000	4.2	6.0	6.0 HP, 230V, 3Ø, 18.5A	General	NEMA L15-20P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	670 lb.	550 lb.
2000	4.2	6.0	6.0 HP, 460V, 3Ø, 12.0A	General	NEMA L16-20P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	670 lb.	550 lb.
2000	4.2	6.0	6.0 HP, 208V, 1Ø, 29.9A	General	NEMA L6-30P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	670 lb.	550 lb.
2000	4.2	6.0	6.0 HP, 208V, 1Ø, 21.0A	General	NEMA L15-30P	10.0 gallons	2.76 gph	386,400	57x30x41.5in.	670 lb.	550 lb.
3000	3.9	8.0	8.0 HP, 230V, 1Ø, 39.5A	AR	NEMA 6-50P	10.0 gallons	2.14 gph	341,800	57x30x41.5in.	700 lb.	580 lb.
3000	3.9	8.0	8.0 HP, 230V, 1Ø, 39.5A	General	NEMA 6-50P	10.0 gallons	2.14 gph	341,800	57x30x41.5in.	700 lb.	580 lb.
3000	3.9	8.0	8.0 HP, 230V, 3Ø, 22.5A	General	NEMA L15-30P	10.0 gallons	2.14 gph	341,800	57x30x41.5in.	700 lb.	580 lb.
3000	3.9	8.0	8.0 HP, 460V, 3Ø, 14.0A	General	NEMA L16-20P	10.0 gallons	2.14 gph	341,800	57x30x41.5in.	720 lb.	600 lb.
3000	3.9	8.0	8.0 HP, 575V, 3Ø, 12.0A	General	NEMA L17-30P	10.0 gallons	2.14 gph	341,800	57x30x41.5in.	720 lb.	600 lb.
3000	3.9	8.0	8.0 HP, 208V, 1Ø, 43.0A	General	NEMA 6-50P	10.0 gallons	2.14 gph	341,800	57x30x41.5in.	700 lb.	580 lb.
3000	3.9	8.0	8.0 HP, 208V, 3Ø, 25.5A	General	NEMA L15-30P	10.0 gallons	2.14 gph	341,800	57x30x41.5in.	700 lb.	580 lb.
3000	4.8	10.0	10.0 HP, 230V, 1Ø, 46.5A	General	NEMA 6-50P	10.0 gallons	3.06 gph	428,400	57x30x41.5in.	704 lb.	584 lb.
3000	4.8	10.0	10.0 HP, 230V, 3Ø, 27.5A	General	NEMA L15-30P	10.0 gallons	3.06 gph	428,400	57x30x41.5in.	704 lb.	584 lb.
3000	4.8	10.0	10.0 HP, 460V, 3Ø, 16.5A	General	NEMA L16-20P	10.0 gallons	3.06 gph	428,400	57x30x41.5in.	724 lb.	604 lb.
3000	4.8	10.0	10.0 HP, 575V, 3Ø, 14.0A	General	NEMA L17-30P	10.0 gallons	3.06 gph	428,400	57x30x41.5in.	724 lb.	604 lb.
3000	4.8	10.0	10.0 HP, 208V, 1Ø, 50.7A	General	NEMA 6-50P	10.0 gallons	3.06 gph	428,400	57x30x41.5in.	704 lb.	584 lb.
3000	4.8	10.0	10.0 HP, 208V, 3Ø, 31.5A	General	NEMA L15-50P	10.0 gallons	3.06 gph	428,400	57x30x41.5in.	704 lb.	584 lb.

### Options:

PART NUMBER	DESCRIPTION	FITS MODELS
	<b>Stainless-steel bottom wrap</b> - Converts powder coated painted bottom wrap to stainless-steel	All models
	<b>Skid feet</b> - Stationary applications	All models
	<b>250°F steam</b> - Increases outlet temperature to 250°F	
	<b>250°F steam</b> - Increases outlet temperature to 250°F	1000 & 2000-PSI models
	<b>250°F steam</b> - Increases outlet temperature to 250°F	
	<b>Skid frame/roll cage design</b> - Stationary applications	All models
	<b>Wireless remote</b> - EZ-quip install	All models
	<b>K7 unloader, flow activated (auto start/stop N/A)</b> - Converts pressure trapping unloader system to flow actuated K7 unloader	
	<b>K7 unloader, flow activated (auto start/stop N/A)</b> - Converts pressure trapping unloader system to flow actuated K7 unloader	

### Accessories:

PART NUMBER	DESCRIPTION	FITS MODELS
	<b>Stack adapter</b> - Allows 8-inch flue pipe to be installed to boiler exhaust port	All models
	<b>Gasket (for stack adapter)</b> - Seals between stack adapter and boiler housing	All models



NEMA 5-20P, 20-amp plug



NEMA L15-20P, 20-amp plug



NEMA L16-20P, 20-amp plug



NEMA L6-30P, 30-amp plug



NEMA 6-30P, 30-amp plug




NEMA L15-30P, 30-amp plug



NEMA L17-30P, 30-amp plug



NEMA 6-50P, 50-amp plug



NEMA L15-50P, 50-amp plug